



Typical MicroLimpet junction box with 3-way temperature switch (Series 2)

MicroLimpet ELECTRICAL HEATER

A COMPACT ELECTRICAL DEVICE FOR HEATING INDUSTRIAL EQUIPMENT, SUCH AS PUMPS, VALVES, METERS AND FLANGES

The patented **Limpet** heating system consists of a range of compact, intelligent, microprocessor-controlled and waterproof heating modules that can be fitted on a wide range of equipment to provide heat for industrial processes or frost protection. The **MicroLimpet™** is a self-contained heating unit with a range of temperature set points and is attached to the equipment using a profiled aluminium adaptor block that transmits the heat into the workpiece body, as well as acting as a heat storage device. The system is designed to help ensure that in the event that a liquid that requires heating stops flowing through the equipment, it does not become too viscous and block the flow. The **MicroLimpet** can be supplied in either 110Vac or 230Vac versions and can deliver up to 120W.

Applications

- Process industries
- Food & beverage
- Pharmaceutical
- Chemical
- Cosmetics
- Frost protection

Advantages

- No control panel required
- Temperature control to $\pm 5^{\circ}\text{C}$ or $\pm 2^{\circ}\text{C}$.
- Option for temperature adjustment
- Compact design
- IP67 rating

MICROLIMPET FEATURES

The main features of the **MicroLimpet** heating system are as follows:

Operation:

- Adjustable temperature range up to 250°C. For temperatures above 120°C, contact the manufacturer.
- 110 / 230 Volts AC; up to 120W power output.
- IP67 flexible conduit connectors for power in.
- Two through-body tubes into which M6 screws are inserted for securing unit to workpiece or adaptor block.
- An insulated jacket is essential for maximum performance and even temperature distribution.

Temperature Control:

The **MicroLimpet** is available in three different versions:

- Series 1, in which the desired product temperature (from 25°C to 250°C) is specified by the user and set by the factory.
- Series 2, in which 2 temperatures (from 25°C to 250°C) are specified by the user. The unit is supplied with a separate junction box with a 3-way rotary switch, so that the user can set the desired temperature (on/off and the desired operating temperatures, normally 20°C apart).
- Series 3, which uses analogue or digital control to provide variable and more accurate temperature control. The unit is supplied with a separate junction box with a suitable controller.

Robust Construction:

- The product is sealed and potted to ensure that all the

TECHNICAL INFORMATION

- Dimensions: 153mm long (excluding connectors) x 40mm wide x 50mm high.
- Voltage: 110VAC or 230VAC.
- Power ratings at 230VAC: 62W or 120W (Series 1) or up to 62W (Series 2 & 3).
- Power ratings at 110VAC: 108W or 120W (Series 1) or up to 108W (Series 2 & 3).
- Temperature range: 0°C to 250°C.
- Ambient: -30°C to +90°C.
- Temperature control: ±5°C (per set point on the Series 1 & 2) or ±2°C for Series 3.
- Ingress protection: IP67. IP68 upon request.
- Colour: Red.



ORDERING INFORMATION

MicroLimpet

Model						
ML						
	Series					
	1					
	2					
	3					
		Code	Voltage			
		11	110 Vac			
		23	230 Vac			
		Connections				
		Code	Type			
		C	Conduit: standard 50cm			
		Internal Sensor				
		Code	Type			
		0	None			
		S	Yes			
		Target Product Temp °C*				
			Temp range	Series		
			1°C	1		
			1°C1/°C2	2		
ML	3	23	C	0	/50/70	Example

* The target product temperature (Series 1&2) can be one of the following:

30, 40, 50, 60, 70, 80, 120 °C

For higher temperature options please contact supplier.

Cable Connections (non-standard)

Code	Type
C	Conduit: standard 75cm *
P	Phoenix: standard 50cm
	C non-standard length (cm)
	100
	125
	150
	175
	200
	P Extra-long (cm)
	150
C	100 Example

* For conduit the mains cable will be 25cm longer

Adaptor Blocks (excluding OmegaLimpet)

Model		
AB		
	Pipe Diameter	
	00	Flat
	50	mm
	76	
	80	
	100	
	120	
	Other	Custom - Specify diameter in mm
		Length Type
		250 Standard in mm
		Other Custom - Specify diameter in mm
AB	80	250 Example

The Limpet Heating Company Limited

Registered Office: 9 Thorne Road,
Doncaster, DN1 2HJ
United Kingdom

Tel: +44 (0) 7837 337570

E-mail: sales@limpetheating.com
www.limpetheating.com